

# TUMBLE DRYERS

TTD 20 · 40 · 60 · 110



## STANDARD FEATURES & BENEFITS

- Industrial tumble dryer
- Stainless steel drum for long life and to avoid corrosion
- Fully insulated, energy-saving drum
- Reversing drum for efficient drying of large items
- Wide hatch sliding doors for easy loading & unloading with window
- Large and easily accessible and removable stainless steel filter with window for visual management
- Hinged lint filter door for easy opening & cleaning
- Flexible and freely programmable control with large display for easy operation and perfect management of your laundry business
- Clear status light indication for easy and quick visual management
- Adjustable feet (fixed on TTD 110)
- Forward tilting on TTD 110 for easy unloading
- Sprinkler device for fire suppression on all gas tumblers
- Sail switch on all models for efficient drying
- Electric solenoid valve on TTD 20 · 40 · 60
- Pneumatic steam valve on TTD 110
- Fresh air intake flap for cool down on TTD 110 steam
- Standard Inverter drive

## OPTIONS

- Residual moisture control + variable speed for perfect drying of delicate linen
- Pneumatic steam valve on TTD 20 · 40 · 60
- Fresh air intake flap for fast cool down on TTD 20 · 40 · 60
- Adjustable speed of the drum
- Heat recirculation for more efficient drying and lower energy consumption
- Sprinkler device for fire suppression on steam heated models
- Steam inlet hose
- Stainless steel high pressure steam coil (max. 12 bar)
- Infrared sensor

TOLON

# TUMBLE DRYERS TTD

TTD 20 · 40 · 60 · 110

MODEL	UNIT	TTD 20	TTD 40	TTD 60	TTD 110	
Dry load	kg	20	40	60	110	
Performance	kg/h	35	67	100	185	
Evaporation Gas/Steam	l/h	18	35	50	95	
Cycle time	min	30	30	30	30	
<b>DRUM</b>						
Drum diameter	mm	990	1230	1230	1362	
Drum depth	mm	563	712	990	1635	
Drum volume	l	433	846	1176	2380	
<b>DOOR (SLIDING)</b>						
Door opening Ø	mm	615	725	725	885	
<b>HEATING</b>						
Electric	kW	20	36	45	-	
Steam	bar	4-6	4-6	4-6	4-6	
Gas	bar	optional 10-12	optional 10-12	optional 10-12	optional 10-12	
	kW	30	50	55	120	
<b>ELECTRIC</b>						
Motor	kW	0,75	1,5	1,5	7,5	
Fan	kW	1,1	3	3	5,5	
Electric consumption*	kW/h	-	-	-	-	
<b>STEAM</b>						
Steam valve connection Ø	DN-BSP	25-1"	25-1"	25-1"	50-2"	
Steam condenser Ø	DN-BSP	20-¾"	25-1"	25-1"	25-1"	
Steam pressure	kPa	400-600	400-600	400-600	400-600	
Steam consumption*	kg/cycle	40	80	120	180	
<b>GAS</b>						
Gas connection Ø	DN-BSP	20-¾"	20-¾"	20-¾"	25-1"	
Gas pressure	mbar	20-200	30-300	30-300	100-300	
Gas consumption*	m³/h	1,9	3,1	3,9	9,5	
<b>EXHAUST</b>						
Exhaust connection Ø	mm	200	200	200	305	
Airflow	Electric	m³/h	1200	3000	3000	
	Steam/gas	m³/h	1500	4200	4200	
					9000	
<b>PROGRAMMABLE CONTROL</b>						
3 default programmes (max 20)		Std	Std	Std	Std	
LCD display 80 x 50 mm		Std	Std	Std	Std	
<b>DIMENSIONS (WxDxH)</b>						
Standard	Electric	mm	1166 x 1337 x 1873	1416 x 1520 x 2138	1416 x 1793 x 2138	-
	Steam	mm	1166 x 1337 x 1906	1416 x 1520 x 2344	1416 x 1793 x 2344	1607 x 2729 x 2537
	Gas	mm	1166 x 1337 x 1971	1416 x 1520 x 2225	1416 x 1793 x 2225	1607 x 2729 x 2488
Packing	Electric	mm	1200 x 1450 x 1950	1450 x 1550 x 2200	1450 x 1800 x 2200	-
	Steam	mm	1200 x 1450 x 1980	1450 x 1550 x 2406	1450 x 1800 x 2406	1620 x 2750 x 2700
	Steam coil	mm	-	-	-	500 x 1650 x 1000
	Gas	mm	1200 x 1450 x 2050	1450 x 1550 x 2287	1450 x 1800 x 2287	1620 x 2750 x 2640
	Combustion chamber	mm	-	-	-	970 x 1330 x 720
<b>WEIGHT</b>						
Net	Electric	kg	430	615	668	-
	Steam	kg	420	650	670	1930
	Gas	kg	455	610	660	1830
Gross	Electric	kg	450	640	695	-
	Steam	kg	438	675	700	1854
	Steam coil	kg	-	-	-	180
	Gas	kg	480	635	690	1854
	Combustion chamber	kg	-	-	-	83
<b>SOUND LEVEL</b>						
	db(A)		< 75	< 75	< 75	< 75

\* Consumption figures with 100% cotton and 50% initial moisture dried to 0%

TOLON reserves the right to make changes to the machines and the specifications in this datasheet at any time, without prior notice. Details and photographs are only for informational purposes and are never binding.

[www.tolon.com](http://www.tolon.com)

TOLON