Dryer - Professional proLite



starLine



Quick and easy: This is the Schulthess proLite Collection. This collection is made for small businesses – such as launderettes – and has everything that makes it indispensable for these industries. With tools specially developed for them, dispensing detergent, doing the laundry and paying for washing are child's play. This is Schulthess magic.

Models







starLine prime TC Stone MGA1.109



starLine TC Stone MGA0.109

Model name	starLine prime+ TC	starLine prime TC	starLine TC
Housing color	Carbon	Stone	Stone
Panel color	Ink	Ink	Ink
Nominal capacity kg	7	7	7
Door hinge	selectable I/r	selectable I/r	right
Supply voltage V	400	400	230
Favorite button	•	•	
Standard drying programs	•	•	•
Special drying program groups	2 Proficlean Wetclean	2 Proficlean Wetclean	0

Technical data Dryer starLine

Brand names		Schulthess		Schulthess
Model name		starLine prime+ TC starLine	prime TC	starLine TC
Product number		MGA1.110 MGA1.109		MGA0.109
Basic data				
Drying technology		Condensation dryer		Condensation dryer
Height	cm			85
Width	cm			60
Depth (including wall clearance)	cm			64
Depth with door open (including wall clearance)	cm			122
Weight empty	kg	47		47
Nominal capacity	kg			7
Filling opening (front)	cm	36/31		36/31
Energy efficiency class				
Condensation efficiency class				
Energy consumption per year	kWh			
Power consumption when switched off / not switched off	W			
Airborne noise emission	dB(A)			
Weighted condensation efficiency	%			
Average condensation efficiency	%			
Program duration (standard cotton program) for the energy label				
Supply voltage	V	400 2N		230 1N
Mains frequency 50 Hz		•		•
Connected loads	kW	2.8		2.1
Fuse protection	А	10		10
Connection cable	mm²	2LNPE 1.5		1LNPE 1.5
Flex		W		W
T12 plug (230V / 10A)				W
T15 plug (400V / 10A)		W		
CEE 7/7 type E+F – Schuko plug (230V/16A)				W
Type I – China plug (230V / 10A)				
Country of manufacture		CH		CH
Features				
LED drum lighting				
Reverse (T27 → Reverse light)				
Pollen filter				
Drying basket				
Without electric heating				
With electric heating		•		•
Door design push to open				
Door design pull to open		•		•
Door hinge on the right (standard)		W		•
Door hinge on the left		W		
Connectivity		0		
Connectivity with RFID and Ethernet				
CRM (Card Reader Module)				
Additional appliance data				
Name and address of provider		Schulthess Maschinen AG, CH-6330 Cham ZG		Schulthess Maschinen AG, CH-6330 Cham ZG

Explanations • = permanently integrated O = optional W = selectable

