Dryer - Professional proLite



topLine



Quick and easy: This is the Schulthess proLite Collection. This collection is made for small businesses – such as launderettes – and has everything that makes it indispensable for these industries. With tools specially developed for them, dispensing detergent, doing the laundry and paying for washing are child's play. This is Schulthess magic.

Models







topLine TC Stone MTA0.109



topLine TW Stone MQA0.109

topLine TA	topLine TC	topLine TW
Stone	Stone	Stone
Ink	Ink	Ink
8	8	8
selectable I/r	selectable I/r	selectable I/r
230	230	230
•	•	•
0	0	0
	Stone Ink 8 selectable I/r 230	Stone Stone Ink Ink 8 8 8 selectable I/r selectable I/r 230 230

Technical data Dryer topLine

Brand names		Schulthess	Schulthess	Schulthess
Model name		topLine TA	topLine TC	topLine TW
Product number		MWA0.109	MTA0.109	MOA0.109
Basic data				
Drying technology		Vented dryer	Condensation dryer	Heat pump dryer
Height		90	90	90
Width		63	63	63
Depth (including wall clearance)		84	84	84
Depth with door open (including wall clearance)		146	146	146
Weight empty		73	88	88
Nominal capacity		8	8	8
Filling opening (front)	cm	36/31	36/31	36/31
Energy efficiency class				
Condensation efficiency class				
Energy consumption per year	kWh			
Power consumption when switched off / not switched off	W			
Airborne noise emission	dB(A)			
Weighted condensation efficiency	%			
Average condensation efficiency	%			
Program duration (standard cotton program) for the energy label				
Supply voltage	V	230 1N	230 1N	230 1N
Mains frequency 50 Hz		•	•	•
Connected loads	kW	2.2	2.3	1.4
Fuse protection		10	10	10
Connection cable		1LNPE 1.5	1LNPE 1.5	1LNPE 1.5
Flex		W	W	W
T12 plug (230V / 10A)		W	W	W
T15 plug (400V / 10A)				
CEE 7/7 type E+F – Schuko plug (230V / 16A)		W	W	W
Type I – China plug (230V / 10A)		**	**	**
Country of manufacture		CH	CH	CH
Country of manufacture		CII	CIT	CH
Features				
LED drum lighting				
Reverse (T27 → Reverse light)		•	•	•
Pollen filter				
Drying basket				
Without electric heating				•
With electric heating		•	•	
Door design push to open				
Door design pull to open		•	•	•
Door hinge on the right (standard)		W	W	W
Door hinge on the left		W	W	W
Connectivity		0	0	0
Connectivity with RFID and Ethernet		0	0	0
CRM (Card Reader Module)		0	0	0
Characteristics (Financial Modelle)			Ŭ	
Additional appliance data				
Name and address of provider		Schulthess Maschinen AG, CH-6330 Cham ZG	Schulthess Maschinen AG, CH-6330 Cham ZG	Schulthess Maschinen AG, CH-6330 Cham ZG

Explanations • = permanently integrated 0 = optional W = selectable

