Washing machine – Professional proLite starLine





Quick and easy: This is the Schulthess proLite Collection. This collection is made for small businesses – such as launderettes – and has everything that makes it indispensable for these industries. With tools specially developed for them, dispensing detergent, doing the laundry and paying for washing are child's play. This is Schulthess magic.

Models – All machines are equipped with a stainless steel wash drum.



starLine prime+ Carbon AEA1.110







starLine Stone AEA0.109

Model name	starLine prime+	starLine prime	starLine
Housing color	Carbon	Stone	Stone
Door color	Ink	Ink	Ink
Nominal capacity kg	7	7	7
Spin speed rpm	1400	1400	1400
Door hinge	selectable l/r	selectable l/r	left
Supply voltage V	400	400	230
Aquasafe			
Aquastop	selectable	selectable	
Favorite button	•	•	
Standard washing programs	•	•	•
Special washing program groups	3 Proficlean Wetclean Disinfection	3 Proficlean Wetclean Disinfection	0

Technical data Washing machine starLine

irand names	Schulthess starLine prime+ starLine prim	Schulthess starLine
roduct number	AEA1.110 AEA1.109	AEA0.109
וטמכנ המחשפו	ALAI.IIU ALAI.IUS	ALAU.105
asic data		
	kg 7	7
leight c	m 85	85
√idth c	m 60	60
	m 67	67
epth with door open (including wall clearance) c	m 110	110
/eight empty	(g 90	90
Filling opening c	m 34	34
pin speed rp	m 1400	1400
nergy efficiency class (A to	5)	
pin efficiency class (A to	5)	
irborne noise emission class (A to l		
nergy efficiency index (Efficiency index		
nergy consumption per year kW		
ater consumption per operating cycle	1	
irborne noise emission during spinning dB (,	-	
rogram duration (rated capacity) for the energy label	4)	
upply voltage	V 400 2N	230 1N
	• 400 ZN	
lains frequency 50Hz		•
lains frequency 50/60Hz		2.2
	W 4	2.3
	A 10	10
	W 1.9/1.9	2.1/-
	n² 2LNPE 1.5	1LNPE 1.5
lex	W	W
12 plug (230V / 10A)		W
15 plug (400V / 10A)	W	
EE 7/7 type E+F – Schuko plug (230V / 16A)		W
ype I – China plug (230V / 10A)		
S1363 – UK plug (230V / 13A)		
ountry of manufacture	СН	СН
ower consumption in		
off mode	W	
standby mode	W	
time preset	W	
connected standby mode	W	
eatures		
irculation pump		
rain pump	W	W
rain valve	W	W
ED drum lighting		
irt sensor		
oad/dosing display (load measurement)		
coustic package		
/ater connection UK (WRAS components)		
-way valve (sluice)		
oor hinge on the left (standard)	W	•
oor hinge on the right	W	
/ater inlet hose (Aquaprotect)	W	•
quasafe		
quasare quastop	W	
asseranschluss UK		
dditional valve for hot water connection	0	
dditional valve for hot water connection dditional valve for soft/rainwater connection	0	
	0	
onnectivity	0	
onnectivity with RFID and Ethernet		
RM (Card Reader Module)		
onnection for 8 liquid detergent dosing pumps	0	
oor bellows EPDM (Standard)	W	W
oor bellows silicone	W	W
oor concept SMAG Homecare		
	•	•
por concept SMAG proLite		
oor concept SMAG proLite		
oor concept SMAG proLite dditional appliance data	Schulthess Maschinen AG,	Schulthess Maschinen AG.

Explanations • = permanently integrated 0 = optional W = selectable

The standardised product declaration complies with the guidelines issued by the FEA Swiss Association of Household and Commercial Appliances in cooperation with consumer organisations. The product declaration is based on the standards of the IEC International Electrotechnical Commission (Technical Commission TC 59).

